



Archived Content

Information identified as archived is provided for reference, research or recordkeeping purposes. It is not subject to the Government of Canada Web Standards and has not been altered or updated since it was archived. Some of this archived content is available only in one official language. Translation by CMHC can be requested and will be provided if demand is sufficient.

Contenu archivé

Le contenu identifié comme archivé est fourni à des fins de référence, de recherche ou de tenue des dossiers; il n'est pas assujetti aux normes Web du gouvernement du Canada. Aucune modification ou mise à jour n'y a été apportée depuis son archivage. Une partie du contenu archivé n'existe que dans une seule des langues officielles. La SCHL en fera la traduction dans l'autre langue officielle si la demande est suffisante.

COMPETITION SERIES

Project #: 133 Both Number of Sheets: 2
Architect: CMHC, in-house,
1954

Number of Storeys: 1, Bungalow--no car accommodation
Single detached

Number of Bedrooms: 2

Fireplace? no,

Basement: -Crawlspace
-

Cladding:

Primary: Horizontal siding, unspecified
-

Secondary: N/A
-

Other: Facebrick on chimney

Roof:

Materials: Asphalt shingles,

Shape: Gable

Special Features: Large attic space with disappearing stair
-

N/A
-

N/A
-

N/A
-



NOTES:-

DIMENSIONS ARE TAKEN TO $\frac{1}{2}$ OF INTERNAL PARTITIONS AND TO OUTSIDE FACE OF EXTERNAL WALL STUDS.

TOP OF ALL SASH TO BE 6'-10" ABOVE FLOOR LINE.

ALL FOOTINGS TO EXTEND BELOW FROST LINE AND REST ON UNDISTURBED SOIL. FOOTINGS TO BE INCREASED IF REQUIRED BY LOCAL SOIL CONDITIONS. SEE N.W.A. 1954 HOUSING STANDARDS

ALL LINTELS TO BE PLACED ON EDGE,
SHELVES & RODS IN ALL CLOSETS.
5 SHELVES IN LINEN CLOSET.

JOISTS TO BE DOUBLED UNDER BRN^g PARTITIONS RUNNING PARALLEL TO FLOOR JOISTS.

OTHER STOCK SIZE WINDOWS MAY BE SUBSTITUTED, PROVIDED GLASS AREA IS A MIN. OF 10% OF THE FLR. AREA OF THE ROOM^g (SERVED.

NUMBER OF ELECTRICAL OUTLETS MUST MEET MIN. STDS. AND COMPLY WITH LOCAL CODES.

THICKER INSULATION MATERIAL MAY BE NECESSARY IN CERTAIN LOCALITIES TO PROVIDE THE REQUIRED RESISTANCE TO HEAT FLOW FOR SUCH AREA.

THE STRUCTURAL MEMBERS ARE DESIGNED FOR A LIVE LOAD OF 30 lbs. PER. SQ. FOOT. IN AREAS WHERE A ROOF LOAD IN EXCESS OF THE DESIGN LOAD IS EXPECTED, IT WILL BE NECESSARY TO REDESIGN THE STRUCTURAL MEMBERS ACCORDINGLY.

ALL STRUCTURAL MEMBERS WILL BE NO. 1. CONSTRUCTION GRADE AND EASTERN SPRUCE SPECIES UNLESS OTHERWISE NOTED ON THE DRAWINGS.

DATE	REVISIONS	BY	CENTRAL MORTGAGE AND HOUSING CORPORATION
10-5-54	REVISED	DR	
any/54	STORAGE ADDED TO GROUND FLOOR KITCHEN - UTILITY DELETED	WJ	
any/54	WALLS ADJUSTED AT BEAM CHANGED	WJ	
11/1/54	REVISED	WJ	DESIGN NO. 10-10-54
2/24/61	REVISED	ENT	133 10-2
3/1/61	DESIGN NO. 10-10-54		
ARCH.	200		DATE 10-10-54 (APRIL)
			SCALE 1/4" = 1'-0"



NO. 1	REVISED	PR	1075	1075	1075
NO. 2	FRONT ELEVATION ALTER	WT	1075	1075	1075
NO. 3	REVISED	DC	1075	1075	1075
NO. 4	REVISED	WT	1075	1075	1075
			DESIGN NO.	WG. NO.	
			133	2 of 2	
			DATE	1954	
			SCALE	1/4" = 1'-0"	